

## GEZE TS 5000 L

### Overhead closer for single-leaf doors

#### Product features

- ▶ Door closer EN 1154 A with guide rail BG (for mounting on opposite hinge side)  
Option: GEZE T-Stop guide rail BG with integrated opening restrictor
- ▶ Adjustable closing force size 2-6
- ▶ Optical size indicator
- ▶ Back check, hydraulic latching action and thermo-constant closing speed adjustable
- ▶ All functions adjustable from front




Fig. 21-1

#### Applications

- ▶ For single action doors, leaf width up to 1400 mm
- ▶ Can be used for right and left hand doors without adjustment
- ▶ For smoke and fire doors (if door mount, a mounting plate is usually required)

#### Specification text

GEZE Overhead door closer TS 5000 L to be mounted to smoke and fire doors, in accordance with EN 1154 A, size 2-6, with guide rail BG, closing force adjustable at front, closing speed and latching action, with visual size indicator, standard mounting on opposite hinge side / door mount, with mounting plate.

#### Optional:

( ) with T-Stop guide rail BG, with integrated opening restrictor

#### Colour:

( ) silver

( ) dark bronze

( ) white

( ) RAL ...

#### Standard version/package

GEZE TS 5000 L closer complete with mounting material and fitting template (mounting plate not included); still needed: guide rail BG with lever

#### ► Version GEZE TS 5000 L with mechanical hold-open

(in Germany not permitted for use with smoke and fire doors)

Installation of the hold-open device in the standard guide rail allows infinitely variable door hold-open between 80° and 130°.

The retaining force for the hold-open can be adjusted.

The hold-open can therefore be disabled.



GEZE TS 5000 L · debitel Zentrale, Stuttgart

### Mounting on opposite hinge side/ door mount with guide rail BG

Example showing the mounting of  
GEZE TS 5000 L, see Fig. 23-1

Section A =

mounting with mounting plate and  
mounting bracket

Section B =

mounting with mounting plate,  
flush door

### Mounting with mounting plate

Dimensions mounting plate,  
see Fig. 17-2




Fig. 23-1

Mounting dimensions for  
left hand door, see Fig. 23-2

right hand door, see Fig. 23-3

### Direct mounting

(in Germany not permitted for use with  
smoke and fire doors)

Mounting dimensions for  
left hand door, see Fig. 23-5

right hand door, see Fig. 23-6

### Mounting bracket

for guide rail BG, see Fig. 23-6




Fig. 23-2





Fig. 23-3

### Attention!



Restrict the max. door opening  
angle with a door stop!  
With TS 5000 L the GEZE T-Stop  
guide rail with integrated opening  
restrictor can be used instead of  
a conventional door stop which  
has to be installed on the floor.




Fig. 23-4




Fig. 23-5




Fig. 23-6




Fig. 24-1

**Mounting on hinge side / frame mount**  
(only permitted for use with smoke and fire doors if the door is officially approved for this mounting method)

Example showing the mounting of  
GEZE TS 5000 L, see Fig. 24-1

Section A =  
mounting with mounting plate  
(dimensions of mounting plate,  
see Fig. 17-2)  
Section B =  
mounting without mounting plate




Fig. 24-2




Fig. 24-3

### Mounting with mounting plate

Mounting dimensions for  
left hand door, see Fig. 24-2  
right hand door, see Fig. 24-3

### Direct mounting

(in Germany not permitted for use with  
smoke and fire doors)

Mounting dimensions for  
left hand door, see Fig. 24-4  
right hand door, see Fig. 24-5




Fig. 24-4




Fig. 24-5

## GEZE TS 5000 L – Ordering information

Description	Finish	ID No.
GEZE TS 5000 L, size 2-6 Door closer without guide rail, without lever	silver	027351
	dark bronze	029399
	white RAL 9016	029400
	RAL colour	027352
Guide rail BG with lever (for mounting on opposite hinge side)	silver	025655
	dark bronze	029403
	white RAL 9016	029404
	brass effect	-
	stainless steel effect <sup>2)</sup>	028732
	RAL colour	025656
Guide rail with lever, height adjustment $\pm 2$ mm	silver	115193
	RAL colour	115194
Guide rail (standard version) with lever (for transom mounting on hinge side)	silver	068221
	dark bronze	068222
	white RAL 9016	015695
	brass effect	067985
	stainless steel effect <sup>2)</sup>	014945
	RAL colour	000773
Guide rail (standard version) with lever, height adjustment $\pm 2$ mm	silver	115191
	RAL colour	115192
Mechanical hold-open <sup>1)</sup>		017924
Mounting material		
Mounting plate for doors without direct closer mounting	silver	049185
	dark bronze	052351
	white RAL 9016	068627
	galvanised steel	057956
	RAL colour	029176
Mounting bracket for standard guide rail BG	silver	025657
	RAL colour	025658
Accessories		
Cover caps (only suitable for mounting on door leaf)	silver	067724
	dark bronze	067725
	white RAL 9016	067726
	polished brass	072698
	stainless steel	072696
	RAL colour	000756

<sup>1)</sup> in Germany not permitted for use with smoke and fire doors<sup>2)</sup> finish stainless steel effect for dry rooms only